



The Construction and Initial Results of a Demonstration Passive Treatment System for Removing Sulfate at a Site on Vancouver Island, BC

Presented by,

Eric Blumenstein, PE, Golder Associates Inc.

Co-authors,

Ryan Schipper, PE and Jim Gusek, PE






Presentation Overview

- Site Location / Background / Desires
- Traditional Sulfate Removal Technologies
- Biological Sulfate Removal
- Bench Testing (Summer 2011)
- Demonstration System
 - Design (Winter 2011-2012)
 - Construction (Summer 2012)
 - Preliminary Results (October 2012 – May 2013)
- Path Forward



Site Location / Background / Needs

- Underground coal mine
- Active workings
- Inactive workings
- Seep into freshwater lake
- Mining influenced water:
 - Sulfate
 - Iron
 - Arsenic
- Desire for:
 - Low long-term operating and maintenance costs
 - Operate in cool weather
 - Fit on available land



SULFATE REMOVAL TECHNOLOGIES





Traditional Sulfate Removal Technologies

- Reverse Osmosis (RO)
Membrane Filtration:
 - Proven technology
 - Capital cost
 - Operating and maintenance cost
 - Labor
 - Chemicals
 - Power
 - Equipment maintenance
 - Brine production / disposal






Traditional Sulfate Removal Technologies



- Chemical Precipitation
 - Barium chloride
 - Lime
 - Proven technology
 - Capital cost
 - Operating and maintenance cost
 - Labor
 - Chemicals
 - Power
 - Equipment maintenance
 - Sludge production / disposal


Potential New Sulfate Removal Technology

- Biological sulfate removal:
 - Active or passive
 - Not a new concept
 - Biochemical reactors (BCR):
 - Sulfate reducing bioreactors (SRBR)
 - Successive alkalinity producing systems (SAPS)
 - Reducing alkalinity producing systems (RAPS)
 - Limitations:
 - Sulfate reduction is limited by carbon availability
 - Need to sequester reduced sulfate (sulfide)



Potential New Sulfate Removal Technology

- Sulfate biologically reduced to sulfide:
 - Some sulfide forms metal precipitates (metal sulfides)
 - Some adsorbs to surface area on substrate
 - Some sulfide leaves the BCR as sulfide anion or hydrogen sulfide



- Excess sulfide in BCR effluent can:
 - Cause health and safety issue (offgas as hydrogen sulfide)
 - Convert to elemental sulfur upon being re-oxidized
 - Convert back to sulfate upon leaving cell and being re-oxidized



Potential New Sulfate Removal Technology

- Options for “sequestering” excess sulfide:
 - Harvest reduced sulfate in BCR effluent
 - After aeration as elemental sulfur
 - Can be difficult to design and require more continual O&M
 - Mechanical rake/collection equipment
 - Add source of sacrificial iron (sulfide anion binds to iron cation and form iron sulfide precipitate):
 - Add iron prior to BCR
 - Mix iron into BCR substrate
 - Add iron to BCR effluent

BENCH SCALE BIOCHEMICAL REACTOR

Summer 2011






Bench Scale Design / Construction






Bench Scale Results – Sulfate





Bench Scale Results – Sulfide





Bench Testing Conclusions

- Each of the five BCR cells demonstrated that sulfate can be removed to the levels desired (>50% removal)
- While the BCR cells with iron sacrificial iron mixed in to substrate provided acceptable sulfide sequestration in situ, iron levels dropped throughout testing, leading to concerns about iron longevity (6 mo-3 yrs)
- Because of a variety of nuisance parameters present in BCR effluent (BOD, TOC, arsenic, manganese, etc.), it is necessary to include an aerobic polishing step in a demonstration/full-scale system
- Arsenic and manganese levels may increase in BCR cell, another reason why an aerobic polishing step is required
- Maximum operational flexibility must be included (bypass piping)


DEMONSTRATION SYSTEM DESIGN

Fall 2011







Demonstration System – Flow Schematic






Demonstration System – General Piping Arrangement







Demonstration System – Aerobic Polishing System



DEMONSTRATION SYSTEM CONSTRUCTION

Summer 2012





Demonstration System Construction – Feed Pump / Piping





Demonstration System Construction – Unexpected Delays / Bedrock Blasting





Demonstration System Construction – Bypass and Effluent Piping





Demonstration System Construction – BCR Cell






Demonstration System Construction – BCR Cell





Demonstration System Construction – BCR Cell





Demonstration System Construction – BCR Cell






Demonstration System Construction – Sulfide Polish Cell





Demonstration System Construction – Sulfide Polish Cell





Demonstration System Construction – Sulfide Polish Cell





Demonstration System Construction – Aerobic Polish Cell and Settling Pond





Demonstration System Construction – Aerobic Polish Cell and Settling Pond





Demonstration System Construction – Aerobic Polish Cell and Settling Pond





Demonstration System Construction – Effluent Channel




DEMONSTRATION SYSTEM PRELIMINARY OPERATION

October 2012 – May 2013






Demonstration System Preliminary Operation – Flow Rate (L/sec)






Demonstration System Preliminary Operation – pH (standard units)






Demonstration System Preliminary Operation – Oxidation Reduction Potential (mV)






Demonstration System Preliminary Operation – Temperature (degrees Celsius)






Demonstration System Preliminary Operation – Sulfate (mg/L)






Demonstration System Preliminary Operation – Sulfate Loading and Removal Rate (g/m³/day)






Demonstration System Preliminary Operation – Sulfide (mg/L)






Demonstration System Preliminary Operation – Iron (mg/L)






Demonstration System Preliminary Operation – Arsenic (mg/L)






Demonstration System Preliminary Operation – Cobalt (mg/L)






Demonstration System Preliminary Operation – Aluminum (mg/L)





Demonstration System Preliminary Operation – Biochemical Oxygen Demand (mg/L)





Path Forward – Part 1

- Allow demonstration system to operate through end of 2013
- Monitor data as SPC flush completes and adjust operation as necessary
 - Potentially bypass a portion of the flow around the BCR
 - Potentially bypass a portion of the flow around the SPC
 - Adjust flow rate and resulting hydraulic retention time
- Use data from demonstration system to design full scale system
- Construct full scale system in summer 2014 or summer 2015




Path Forward – Part 2

- Operate system indefinitely
 - Drop water level in underground workings to dry up seep
 - Continue operations to maintain low water level in workings
 - Replace BCR substrate as-needed (10-20 yrs)
 - Replace SPC substrate as-needed (5-10 yrs)
 - Remove sludge from AL as-needed (5-7 yrs)

- Look for additional sites to implement/fine tune biological sulfate removal
 - Fully passive system (no pumping, passive aeration)
 - Hybrid system (minimal power and O&M requirement)
 - Fully active system (ICB fixed-film media with carbon/nutrient dosing)

Potential Future of Biological Sulfate Removal



THANK YOU!

Contact information:

eblumenstein@golder.com

