Targeted Maintenance Efforts to Ensure a Decade of Successful Passive Treatment

Robert W. Nairn

Boren Distinguished Professor and Viersen Presidential Professor

CREW Director

Bryan Page, Brandon Holzbauer-Schweitzer,





The UNIVERSITY of OKLAHOMA

Gallogly College of Engineering
School of Civil Engineering and Environmental Science

Center for Restoration of Ecosystems and Watersheds University of Oklahoma

CREW





Tar Creek (OK) Superfund Site

- Tri-State Pb-Zn Mining District
- National Priorities List (1983)
- 137 km² watershed
- Elevated Fe, Zn, Cd, Pb, As in water, soils, wastes, and biota
- Ten Native AmericanTribes
- Mining "mega-site"






Mayer Ranch Passive Treatment System


- USEPA funding 2004-10
- 10 process units
 - 8 in parallel trains
 - Coupled oxidative-reductive mechanisms
 - Solar- and wind-powered re-aeration
- First PTS in entire Tri-State Mining District
- Continuous operation since 11/2008
- Long-term CREW ecological engineering research site

MRPTS Water Quality Changes


	In	Out
рН	5.95	7.02
Tot. Alk. (mg/L)	393	224
Net Alk. (mg/L)	29	224
Fe (mg/L)	192	0.13
Zn (mg/L)	11	0.25
Ni (mg/L)	0.97	0.15
Cd (μg/L)	17	<pql< td=""></pql<>
Pb (μg/L)	60	<pql< td=""></pql<>
As (μg/L)	64	<pql< td=""></pql<>
SO ₄ -2 (mg/L)	2239	2057




Extensive Ability to Manipulate Water Levels and Control Flows (lots of buried pipes)




Extensive Ability to Manipulate Water Levels and Control Flows (lots of valves)



















Water Surface Elevations



- Staff gauges
- Data-recording pressure transducers
 - Solinst Leveloggers
 - Barometric pressure-corrected
 - 30-minute data collection intervals
 - Deployed in every PTS unit and receiving stream

















Pipe is clogged? Snake it!

- Rented sewer snake
- Tried every head attachment known to man
- Cloudy water, but no evidence of clog
- Reestablished flow for a few days/weeks



Pipe is clogged? Jet it!



Pipe is clogged? Let's see...

- Rented sewer camera
- Pipe stained, but no obstruction




Frame size: 720x460 Video codec: mpeo2video(MPEG-2 vid opularity: *****


File type: DVD Video Object File (; VO6) Location: K/Photos (Organized) (Ta. Accessed: February 6, 2018 9159 AM

26ft 11 in

Reestablished flow for a few days/weeks!




What is buried out there?



PTS O&M with Limited (No) budget, No Time and Thoughts to the Future

- Leave existing infrastructure in place, but take off-line
- Open berm and install straight short pipes
- Install inlet (not inline) AgriDrain structures with weirs
- Set identical weir elevations to split flows evenly into C2N/C2S
- Cross our fingers...























Extensive Ability to Manipulate Water Levels and Control Flows



Extensive Ability to Manipulate Water Levels and Control Flows





















What else is buried out there?

Decrease in K over time



What else is buried out there?

Decrease in K over time





Estimated Hydraulic Conductivity (K)


■ Field-falling head tests

Slug tests


Modified single-ring infiltrometer

Laboratory-falling head tests

Field-Falling Head Tests




Field-Falling Head Tests



Slug Test



Modified Infiltrometer






Laboratory Falling Head Tests

Klute and Dirkson (1986)

■ ASTM 28-4.2






Decreases in Hydraulic Conductivity


	K (m/day)	
	C3N VFBR	C3S VFBR
2008 (pre-construction)		
Laboratory-Falling Head	4.77	4.77
2016 (8-years operation)		
Laboratory-Falling Head	0.51	
Field-Falling Head	0.13	0.31
Modified Infiltrometer	0.19	0.17
Slug Test	1.25	0.43

Restore Hydraulic Conductivity!

Flip the Substrate




Intact 9-yr Old Substrate




Little Loss of Depth



Clean Underdrain Stone




Degraded Material Near C3S-In



Substrate Flipped





Substrate Flipped



Proud Co-Author

Field-Falling Head Test





Decreases in Hydraulic Conductivity

	K (m/day)	
	C3N VFBR	C3S VFBR
2008 (pre-construction)		
Laboratory-Falling Head	4.77	4.77
2016 (8-years operation)		
Laboratory-Falling Head	0.51	
Field-Falling Head	0.13	0.31
Modified Infiltrometer	0.19	0.17
Slug Test	1.25	0.43
2017 (after flipping)		
Field-Falling Head	4.5	4.5




Conclusions

- Reestablished surface flow connection between C1 and C2N/C2S
 - Eliminated buried flowpath
 - Installed inlet weir structures
 - One week of down time
- Reestablished C3N/C3S VFBR hydraulic conductivity
 - Flipped organic substrate
 - No evidence of underdrain failure
 - Ten days of down time


"Major" O&M Costs

	C1-C2N/C2S Surface	C3N/C3S VFBR
2 x 8" x 5' Inlet AgriDrains	\$1200	
Equipment (Takeuchi TB153)	\$1500	\$1900
Stone (for ramp)		\$700
Labor	\$1000	\$1500
Misc. (pipe, fuel etc.)	\$700	\$200
Total	\$4400	\$4000

Mayer Ranch PTS - COCs



"Major" O&M < \$10K (\$840/yr) All monitoring and regular O&M ~ \$10K/yr



Southeast Commerce PTS

